



# LIONSHEAD

[www.lionsheadtireandwheel.com](http://www.lionsheadtireandwheel.com)

## NO EXCUSES Guaranteed!

At Lionshead we are so confident in the performance of our tires we will replace **any ST radial tire for any reason** for the first twelve (12) months from date of retail sale.

### Innovative products and services:

- ✓ **Five (5) year warranty** for manufacturer's defect.
- ✓ For first twelve (12) months from date of retail sale Lionshead will replace the tire for any reason under our **No Excuses Guarantee** Program.
- ✓ The assemblies come with a complimentary **two (2) year Roadside Assistance Program**. The owner can use this program to have a service technician come out and remove the damaged assembly and install the inflated spare at any time.
- ✓ All assemblies are **filled with nitrogen**. Nitrogen maintains a tire's proper PSI longer which, in turn, insures the assembly achieves its stated load carrying capacity.
- ✓ Lionshead automotive grade aluminum wheels have **steel inserts** in the lug nut wells. This application improves safety by enhancing proper torque retention.

#### Lionshead Specialty Tire & Wheel

305 Steury Avenue

Goshen, Indiana 46528

Phone: (574) 533-6169





**LIONSHEAD**

# Tire and Wheel Specifications

## Radial Specifications

Size	Ply	Maximum Load (lb)	Pressure
ST145R12 LRD	8	1220	65PSI
ST145R12 LRE	10	1520	80PSI
ST175/80R13 LRC	6	1360	50PSI
ST185/80R13 LRD	8	1710	65PSI
ST205/75R14 LRC	6	1760	50PSI
ST205/75R14 LRD	8	2040	65PSI
ST205/75R15 LRC	6	1820	50PSI
ST205/75R15 LRD	8	2150	65PSI
ST225/75R15 LRC	6	2150	50PSI
ST225/75R15 LRD	8	2540	65PSI
ST225/75R15 LRE	10	2830	80PSI
ST235/75R15 LRC	6	2340	50PSI
ST235/75R15 LRD	8	2910	65PSI
ST235/80R16 LRE	10	3520	80PSI
ST235/85R16 LRE	10	3640	80PSI
ST235/85R16 LRF	12	3690	95PSI
ST235/80R16 LRG	14	4080	110PSI
ST235/85R16 LRG	14	4400	110PSI
LT225/75R16 LRE	10	2680 single/2470 dual	80PSI
LT235/85R16 LRE	10	3420 single/2778 dual	80PSI
LT235/85R16 LRG	14	3750	110PSI
LT315/70R17 LRD	8	3195 single/2910 dual	50PSI
215/75R17.5 LRH	16	4805 single/4546 dual	123PSI
235/75R17.5 LRH	16	6005 single/5675 dual	128PSI
245/70R19.5 LRG	14	4540 single/4410 dual	110PSI

## Aluminum Wheel Specifications

Size	Bolt Pattern	Maximum Load (lb)
12x4	5-4.5	1520
13x5	5-4.5	1710
14x5	5-4.5	2040
15x5	5-4.5	1820
15x6	5-4.5	2200
15X6	6-5.5	2830
16X6	6-5.5	3300
16X6	8-6.5	4080
16X6	8-6.5 HD	4400
17.5x6.75	8-6.5 (9/16")	4850
17.5x6.75	8-6.5 (5/8")	6050

## Steel Wheel Specifications

Size	Bolt Pattern	Maximum Load (lb)
8x7	5-4.5	1075
10x6	5-4.5	1535
12X4	5-4.5	1520
13X4.5	5-4.5	1710
14X5	5-4.5	2040
15X5	5-4.5	1870
15X6	5-4.5	2200
15X6	6-5.5	2830
16X6	6-5.5	3300
16X6	8-6.5	4080
16X6	8-6.5 HD	4400
17.5X6.75	8-6.5 (5/8")	6005